

Full Colour Printer

RICOH
imagine. change.

RICOH P C600

Printer



RICOH
P C600

42
ppm

Monochrome
Full Colour

Vibrant Prints For Your Business Needs

Setting new benchmark in efficiency and outstanding quality colour documents

Accelerated Productivity

RICOH P C600 features an impressive print speed at up to 40 pages per minute for A4 and 42 pages per minute for letter-size, with maximum paper input capacity at 2,100 sheets (including bypass and up to four paper trays), letting you achieve maximum productivity amidst your busy work environment.



User-Friendly Experience

Featuring a sleek 4-line LCD panel, you can now complete your business tasks right at your fingertips with the new RICOH P C600. The panel is also tiltable up to 90 degrees, giving you the best flexibility of viewing the panel at your own comfort. The built-in NFC allows you to print from any of your NFC-enabled devices to the RICOH P C600 whenever needed. The availability of mobile and cloud connectivity provides freedom and versatility for you to print from anywhere, anytime.

Security in our DNA

Recognising your modern business security challenges, RICOH P C600 ensures business information remains secure with robust security layers in place. Manage your confidential documents with the Locked Print function and only release when authentication is done at the device.



Economical and Environmentally Friendly - 2 in 1

The RICOH P C600 benefits from an incredibly low Typical Electricity Consumption (TEC) rating, packed together with a fast warm-up time of 22 seconds, making it a perfect energy-efficient office printer. Built for lasting values, the RICOH P C600 comes with a long-life 300,000-page drum unit which requires minimum maintenance, ensuring your running costs are kept affordable.

RICOH P C600

MAIN SPECIFICATIONS

MODEL	RICOH P C600
GENERAL	
Function	Print
Operation panel	4-line LCD
Warm-up time	22 seconds or less
First output speed : Full colour	6.5 seconds
First output speed : B/W	5.5 seconds
Continuous output speed	40 ppm (A4), 42 ppm (LT)
CPU	Intel® Atom Processor ApolloLake 1.3 GHz
Memory	2 GB standard/maximum
HDD	320 GB maximum (option)
Weight [Mainframe]	Less than 34 kg
Dimensions W x D x H	Standard : 445mm x 570mm x 470mm Maximum : 445mm x 570mm x 818mm (with 3 PFU options)
Power source	220-240V, 50/60Hz
PRINTER	
Printer language	Standard : PCL5c, PCL6, PostScript3 (Emulation), PDF Direct (Emulation) Option : Genuine Adobe® Postscript®3™, PictBridge, XPS
Print resolution	1,200 x 1,200 dpi
Network interface : standard	Ethernet 10base-T/100base-TX/1000base-T, USB2.0, USB Host 2.0
Network interface : option	IEEE802.11a/b/g/n (Wireless LAN), IEEE1284/ECP, Ethernet (RJ-45 network port)
Mobile printing capability	Apple AirPrint®, Mopria®, NFC, RICOH Smart Device Connector
Windows® environments	Windows® 7/8.1/10, Windows® Server 2008/2008 R2/2012/2012 R2/2016
UNIX environments	UNIX Sun® Solaris 10, HP-UX, SCO OpenServer, RedHat® Linux, IBM® AIX
SAP® environments	SAP® R/3®, SAP® S/4®
SECURITY	
Authentications	Windows authentication, LDAP authentication, Basic authentication, User code authentication, 802.1x wired authentication
PAPER HANDLING	
Recommended paper size	A4, A5, A6, B5, B6, Custom sized paper
Paper input capacity	Standard : 500 sheets (excluding bypass 100 sheets) Maximum : 2,100 sheets (std. tray + bypass + optionx3)
Paper output capacity	500 sheets
Paper weight	Standard Tray : 60 - 163g/m ² , Bypass & Option : 60 - 220g/m ² , Duplex : 60 - 163g/m ²
Paper types	Plain Paper, Recycled Paper, Colour Paper, Letterhead, Preprinted Paper, Bond Paper, Label Paper, Envelope, Coated Paper, Middle Thick Paper, Thick Paper, Cardstock
ECOLOGY	
Power consumption	Maximum : 1,550W Ready mode : 88.1W Sleep mode : 3.3W
TEC value	1.9 kWh
INPUT TRAY OPTION	
3 x 500-sheet paper tray (PB1150)	Paper size : A4, A5, B5, B6, Custom size Paper weight : 60 - 220g/m ²
OTHER OPTIONS	
Hard Disk Drive Option Type P17, XPS Direct Print Option Type P17, Camera Direct Print Card Type P17, PostScript3 Unit Type P17, USB Device Server Option Type M19A, IEEE 802.11 Interface Unit Type M24, IEEE 1284 Interface Board Type M19	
CONSUMABLES (ISO)	
Starter toner	K : 8,000 pages C,M,Y : 6,000 pages
Toner (K: Black)	18,000 pages
Toner (C,M,Y: Cyan, Magenta, Yellow)	12,000 pages

RICOH
imagine. change.

RICOH (THAILAND) LIMITED
341 Onnuj Road, Prawet, Prawet, Bangkok, Thailand 10250
Tel: 02 088 8888, Fax: 02 322 9870

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2020 Ricoh Asia Pacific Pte Ltd. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Asia Pacific Pte Ltd.

