

RICOH imagine. change.

RICOH SP C360DNw SP C360SFNw



A compact workhorse for the busy workplace

The SP C360DNw and SP C360SFNw are LED printers that combine quality, speed and reliability with modern workflow capabilities, making them ideal for small to medium businesses and small workgroups.

Featuring an easy-to-use setup wizard and convenient WIFI connectivity, the models are easy to install, ensuring that you can start using the wide range of productivity features on offer, such as double-sided scanning, almost instantly to save time and boost productivity.

Both models offer advanced security with Locked Print to protect confidential documents from unauthorised viewing. Additionally, these printers are eco-friendly with low typical electricity consumption (TEC) values and minimal power consumption in Sleep Mode.

- The SP C360DNw comes with a tiltable 4-line LCD panel for easy viewing and navigation.
- The SP C360SFNw comes with an intuitive 7" Smart Operation Panel, which provides both ease-ofuse and opens up a world of additional functionality.



Working smart has never been simpler

Speed and clarity meets light and compact

- These LED printers can print 1,200 dpi quality documents at 600 dpi speed, enabling you to produce sharper and higher quality documents in a shorter amount of time.
- Because LED technology uses less components to print, these printers are smaller and lighter, making them suitable for a variety of businesses and small spaces.
- Fast print speeds of up to 30ppm and quick first print time of 7.2 seconds (Black and White) and 8.6 seconds (Full Colour) translates into high productivity.

Functionality at your fingertips

- Intuitive operating concept with the tiltable 4-line LCD Display (SP C360DNw) offers an at-a-glance view of useful functions such as network and remaining toner status.
- The 7" touch panel interface (SP C360SFNw) provides you with a full touch screen experience and variety of applications that help you in your business.
- Single Pass Document Feeder with ID card copy/scan functionality allows fast double-sided scanning.
- Carrier Sheet allows easy scanning of irregular-shaped, lightweight,
 fragile and wrinkled documents with accurate double-sided copying capability.

Security and Ease of use

- Both the SP C360DNw / SP C360SFNw come with a set-up wizard that cuts out the need to navigate complex processes.
- Convenient wireless connectivity enables you to set up and use the printers with "Plug & Play-like" simplicity.
- Protect confidential documents from unauthorised viewing with Locked Print, which requires you to enter a password on the operation panel before printing.







Seamless Connectivity

- Print on the go from your smart devices phone, tablet, and notebook with Apple AirPrint[®], Mopria[®] and RICOH Smart Device Connector Smart Device Connector.
- Print directly from USB using the built-in slots without the need to use a computer.
- Gain quick access to the printers via the embedded NFC tag or tap on WIFI Direct without connecting to the corporate network.



RICOH SP C360DNw / SP C360SFNw

| Model | SP C360DNw | SP C360SFNw |
|--|---|---|
| Function General | Print | Print / Scan / Copy / Fax |
| Configuration | Desktop | |
| Panel | 4-Line LCD Display | 7" Smart Operation Panel |
| Duplex | | matic |
| Dimension | 400 x 515 x 360 mm | 420 x 540 x 547 mm |
| Weight Processor | 32.0kg 41.5kg | |
| Memory | Standard/ Max: 512MB | Standard/ Max: 2GB |
| Interface | Standard: Wireless LAN (IEEE 802.11a/b/g/n), Ethernet 10 base- | Standard: Wireless LAN (IEEE 802.11a/b/g/n), Ethernet 10 base- |
| | T/100 base-TX/1000 base-T, USB 2.0, USB 2.0 Host, USB 2.0-Device | T/100 base-TX/1000 base-T, USB 2.0, USB 2.0 Host, USB 2.0-Device, SD slo |
| Mobile Capability | RICOH Smart Device Connector, | |
| Power Consumption (Max) | | Kw 42 Cui |
| Ready Mode Energy Saver (Sleep) | 34.5w 0.78w | 43.6w 1.5w |
| TEC Value | 1,2 kWh | 1.3 kWh |
| Power Source | | 50/60 Hz |
| Energy Star | Cert | ified |
| Print | | |
| Technology | Electro photographic printing system with LED 1-sided Black/Full Color : 30 ppm (A4/SEF, LT/SEF) | |
| Print Speed (A4) | 2-sided Black/Full Color : 2-sided Black/Full Color : 28 pp | |
| Warm Up time | 20 seconds | 25.1 seconds |
| First Print Out Time | | nds, B/W: 7.2 seconds |
| Print Resolution | | 00 x 2,400 dpi equivalent, 1,200 x 1,200 dpi |
| Print Language | Standard: PCL5c, PCL6, PostScript 3 (Emulation), PDF direct (Emulation) | |
| Network Protocol | | |
| Windows [®] environments | Windows® Vista, Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2008R2, Windows® Server2012, Windows® Server 2012R2, Windows® Server 2016 | |
| Mac OS environments | Mac OS X v.10.9 or later | |
| UNIX environments | UNIX Sun [®] Solaris, HP-UX, SCO OpenServer, RedHat [®] Linux, | |
| SAP [®] R/3 [®] environments | SAP® R/3®, | |
| Other Supported environments | AS/400 [®] using OS/400 Host | PrintTransform, IBM iSeries |
| Copy | | Lin to 20 and |
| Copy Speed (A4) Document Feeder Type | - | Up to 30cpm Single Pass Document Feeder (50 sheets) |
| | | Flatbed: 600 x 600 dpi |
| Resolution | - | SPDF: 1,200 x 1,200 dpi |
| Multiple Copy | - | up to 999 |
| Reduction / Enlargement | - | From 25% to 400% in 1% steps |
| Copy Features | - | Image density adjustment (Manual only 9 levels), Copy mode (Text / Photo / Text Photo / Lighten Background), Memory copy, Duplex copy, Combine copy (2 in 1), ID Card Copy, Auto Tray Switch, Directional Size Magnification, Auto Start, User Program, Electronic Sorting, Image Rotation, Series Copy (2 sided -> 1 sided 2 sheets) |
| Scan Scan Technology | | CIS |
| Scan Mode | - - | Color, B&W, Grayscale, Glossy |
| Scan Speed | | Full colour 20ipm(Max) , B/W: 30ipm (Max) |
| Resolution | <u>.</u> | Standard: 100 - 600 dpi |
| | | Default: 200 dpi Single Page JPEG, Single/Multi Page TIFF, Single/Multi Page PDF |
| File Format Bundled Drivers | - | |
| Scan To | - | E-mail, Folder, USB, SD card, SMB |
| Fax | | |
| Circuit | - | PSTN, PBX |
| Compatibility | - | ITU-T (CCITT) G3 |
| Resolution Compression Method | - | 8 x 3.85 line/mm, 200 x 100 dpi, 8 x 7.7 line/mm, 200 x 200 dpi MH. MR. MMR |
| Transmission Speed | - | G3: 3 second(s) (200 x 100 dpi) |
| Modem Speed | - | Max: 33.6 Kbps |
| Scan Page Per Minute | - | 28 pages per minute |
| Memory Backup | - | Yes |
| Paper Handling | | |
| Recommended Paper Size | A4, B5, A5, B6, A6, Legal, Letter, HLT, Executive, F, Foolscap, Folio, 16K, Custom size: (Min) 82.5mm x 148mm (3.25″ x 5.83″), (Max) 216mm x 356mm (8.50″ x 14.01″) | |
| Paper Input Capacity | | : 100 sheets, Max: 850 sheets |
| Paper Output Capacity | Maximum: 200 sheets | Maximum: 150 sheets |
| Paper Weight | Paper tray(s): | |
| | Bypass tray: 56 - 220 g/m² | |
| Options Accessories | Paper Feed Unit TK1230 (250 sheets), | Paper Feed Unit TK1240 (500 choots) |
| Consumables | | Taper reeu onic ricitz40 (500 sneets) |
| | Starter kit: 2 5K (K) | 1.5K (C,M,Y) pages |
| | | |
| All - in - One Toner Cartridges | Toner-HY: 7K (K), | |
| All - in - One Toner Cartridges (ISO/IEC 19798) | Toner-HY: 7K (K), Toner-LY: 2.5K (K), | |



All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2020 Ricoh Asia Pacific Pte Ltd. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Asia Pacific Pte Ltd.





Apple AirPrint



V2-072020

