

B115Z

Multipurpose

Wax-Resin • Flat head

- High scratch and smear resistance
- High sensitivity at low energy levels
- Applicable to a wide range of receiving labels: paper, coated paper, PET/PP/PE/PVC films...
- Ricoh's unique coating on the back allows reliable and superior matching qualities with the thermal head

PRINTING PROPERTIES

Maximum printing speed 10 IPS

	Top-coated paper	PET	PE	PP	PVC
Compatibility	✓	✓	✓	✓	✓

Note: Smoothness Bekk for paper family must be over 200s.

Image resolution for paper and film:

Minimum size:




- For the lines: 0.1mm

- For the characters: 1.0mm

RIBBON PROPERTIES

- Total ribbon thickness: < 9 µm
- Polyester film thickness: 4.5 µm
- Friction coefficient: < 0.035
- Ink melting point: 80°C
- Tearing resistance: > 200N/mm²
- Transmission density: 1.00 mini

CERTIFICATES



Application



Tags



Logistic/Storage
Shipping



Flexible
packaging



Food
ingredient

GENERAL CONDITION


Usage conditions: 5 to 35°C at 20 to 85% of relative humidity.

Storage conditions: Keep indoors avoiding high temperature, high humidity, and direct sunlight.


Storage life: 24 months after slitting day.

RICOH
imagine. change.


SENSITIVITY



RESISTANCE



PRINT QUALITY & DURABILITY



IMS DIVISION

RICOH (THAILAND) LTD

341 Onnuj Road, Prawet, Prawet, Bangkok 10250, Thailand

Tel: 02-088-8888

Email: RTHIMS@Ricoh.co.th Website: www.ricoh.co.th

* Specifications are subjected to change without notice.

* The color(s) of the actual product may vary from the color(s) shown in this datasheet



Scan to visit product's page