





B118W

Economical

- Excellent blackness
- High sensitivity
- Low energy printing

PRINTING PROPERTIES

Maximum printing speed 12 IPS

	Non top-coated paper	Top-coated paper	High gloss paper	Synthetics
Compatibility				 Limited

RIBBON PROPERTIES

- Total ribbon thickness: < 8 μm
- Polyester film thickness: 4.5 μm
- Ink melting point: 65°C
- Friction coefficient: < 0.2

GENERAL CONDITION

Usage conditions: 5 to 35°C at 20 to 80% of relative humidity.

Storage conditions: Keep indoors avoiding high temperatures (Such as beside the heat source), high humidity, and direct sunlight.

Storage life: 24 months after production.

Application



Tags



Logistic/Storage
Shipping



Multi purpose
label




Food
ingredient

PRINTED IMAGE DURABILITY

TESTS	RESULT
Darkness	2.1 ± 0.1
Print quality	ANSI A
Mechanical resistance	level 2 on a scale of 4
Temperature resistance	50°C - 60°C

B118W DURABILITY



These performances are for guidance only. Results are obtained with adapted receiving material and optimum print conditions. (Ricoh test method)

IMS DIVISION

RICOH (THAILAND) LTD

341 Onnuj Road, Prawet, Prawet, Bangkok 10250, Thailand

Tel: 02-088-8888

Email: RTHIMS@Ricoh.co.th Website: www.ricoh.co.th

* Specifications are subjected to change without notice.

* The color(s) of the actual product may vary from the color(s) shown in this datasheet



Scan to visit product's page