

B130ER

Resin

TTO : Thermal Transfer Overprinting

- High speed printing
- Excellent scratch and smear resistance
- Very good alcohol resistance

SPECIFICATIONS

- Base film thickness: $4.0 \pm 1.0 \mu\text{m}$
- Total ribbon thickness : $6.4 \pm 1.0 \mu\text{m}$
- Ink melting point : 105°C

PRINTING CHARACTERISTIC

- Ink Color : Black
- Max printing speed = 250mm/second (*depend on substrate & application*)

RECOMMENDED SUBSTRATES

Films : Flexible Packaging

Application



Flexible
Packaging



Food &
Beverage



Medical



Cosmetic

DURABILITY

Scratch Resistance : Excellent

Smear Resistance : Excellent

Alcohol Resistance : Very good



CERTIFICATES



GENERAL CONDITION

- Usage conditions: 5 to 35°C at 30 to 85% of relative humidity
- Storage conditions: Keep indoors avoiding high temperature, high humidity, and direct sunlight
- Storage life: 24 months after production

IMS DIVISION
RICOH (THAILAND) LTD
341 Onnuj Road, Prawet, Prawet, Bangkok 10250, Thailand
Tel: 02-088-8888
Email: RTHIMS@Ricoh.co.th Website: www.ricoh.co.th

* Specifications are subjected to change without notice.
* The color(s) of the actual product may vary from the color(s) shown in this datasheet



Scan to visit product's page