A4 Digital Mono Laser Printer

RICOH P 310 M 320FB





Stability and Performance

Secure and rapid document sharing even remotely

Share documents remotely with ease

RICOH M 320FB offer a host of features that allow you to share documents quickly in digital format. Simply use the 35-sheet Automatic Reversing Document Feeder (ARDF) to scan that full-colour presentation to your colleagues for review in an instant using any of the multiple Scan-to capabilities, including Scan-to-Email, FTP, Folder, USB drive and more.



*Image shown is with optional tray



Stay productive even when away from the office

Simply download the RICOH Smart Device Connector app to your smartphone or tablet to access and share information. Send print jobs directly to your Ricoh printer from your personal mobile device for fast, convenient mobile printing via Mopria[®] or AirPrint[®]. You can also pair your Android[®] device via the Near Field Communications (NFC) tag on printer once you are back in the office to authenticate and transfer information and print your documents.

Security is in our DNA

Keep your information secure as you transfer and print confidential documents with the robust security layers Ricoh has put in place. Use the Locked Print function to protect documents from unauthorised viewing and have peace of mind knowing that network encryption ensures secure digital data transmission.



RICOH P 310 / M 320FB

MAIN SPECIFICATIO	NS			
MODEL		RICOH P 310	RICOH M 320FB	
GENERAL				
Configuration Technology		Deski Laser (N	· ·	
Function(s)		Print	Print, Copy, Scan, Fax	
Display panel		4-Line operation LCD	4.3" colour touch panel	
Processor		350 MHz	400 MHz	
Memory		128 MB	256 MB	
Mobile capability		RICOH Smart Device Connecto	or, Apple AirPrint®, Mopria®	
Printer language		PCL5e, PCL6, PostScript 3 emulation		
Network protocol		TCP/		
Interface Operating system	Standard	10Base-T/100Base-Tx (Ethernet), USB 2.0 Type A x 1— rear, USB 2.0 Type B x 1— rear, NFC tag	10Base-T/100Base-Tx (Ethernet), USB 2.0 Type A x 2—1 x rear & 1x front, USB 2.0 Type B x 1— rear, NFC tag	
	Optional	IEEE 802.11a/b/g/n/ac (Wirel		
	Windows®	Windows® 8.1, Windows® 10, Windows® Server 2012, Windows®	Server 2012R2, Windows® Server 2016, Windows® Server 2019	
	Mac	Mac OS v10.10 - v11		
	Other	Linux		
PRINTER				
Duplex printing Print speed (A4)		Auto 32 ppm (Simplex), 13 ppm (Duplex)		
First print out time		52 ppm (simplex), 7.1 sec		
Warm up time		26 seconds or less	30 seconds or less	
		600 x 600 dp	i (Default),	
Print resolution		Windows®: 600 x 600 dpi, 1,20 MAC: 600 x	0 x 600 dpi, 1,200 x 1,200 dpi x 600 dpi	
		Linux: 600 x 600 dpi, 1,200 x 1,200 dpi		
Average print volume		700 - 5,800 pages		
Duty cycle		35,000 pages/month		
COPIER			Up to 32 ppm	
Copy speed (A4) Document feeder type			Automatic Reversing Document Feeder	
Document feeder type Document feeder capacity			35 sheets	
Resolution			300 x 600 dpi (ARDF), 600 x 600 dpi (Platen)	
Multiple copy			Up to 99	
			Zoom Range: 25%-400%, Image density: 5 levels, Image quality: Text, Photo, Mixed,	
Copy features		-	Combined Copy, Memory Copy, ID Card Copy, Series Copy	
SCANNER				
Scan speed (A4 ARDF) Resolution		•	Mono: 13 impressions/minute, Colour: 4.5 impressions/minute	
Original size			600 x 600 dpi (ARDF), 1,200 x 1,200 dpi (Platen), 19,200 x 19,200 dpi (TWAIN) A4	
Bundled drivers			Network TWAIN, WIA	
Scan to			Scan to email, Scan to folder, Scan to FTP, Scan to USB, TWAIN scanning	
FACSIMILE				
Circuit		-	PSTN, PABX	
Compatibility		-	T.30 (ITU-T SuperG3)	
Resolution		-	Horizontal: 200 dpi-8dots/mm, Vertical 100 dpi-3.85dots/mm, 200 dpi-7.7dots/mm	
Transmission speed			33.6 Kbps—2,400 bps with automatic shift down	
Compression method		-	MH, MR, MMR	
Reception features		-	Automatic, Paperless fax, Manual, Main scan auto reduction	
Other supported features			Quick dial—8 (20 digits for name, 40 digits for numbers), Speed dial—100 (20 digits fo name, 40 digits for numbers), Label registration for Quick/Speed, Redial—automatic o manual, Redial interval time—2 selections (5 minutes: default, 6 minutes), Only redial last number, Direct fax number entry	
SECURITY			last number, pirect las number entry	
Authentication		Locked	Print	
PAPER HANDLING				
Recommended paper size		A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican Oficio, Indian Legal, Envelopes, Australian Foolscap		
	Standard	250 sheets (Bypass: 50 shee	ts), Maximum: 300 sheets	
Paper input capacity	With optional paper tray	Paper Bank PB1130: 250 she	eets, Maximum 550 sheets	
Paper output capacity		125 sheets	50 sheets	
Paper weight		52 to 162 g/m ²		
ECOLOGY				
Dimensions (W x D x H)		370 mm x 392 mm x 262 mm	405 mm x 392 mm x 420 mm	
Weight Power consumption (Max)		Less than 13.0 kg 1,025 W (Asia Pacific)		
Ready mode		63.8 W (Asia Pacific)	c) 65.7 W (Asia Pacific)	
Energy saver (Sleep)		0.72 W (Asia Pacific)	0.87 W (Asia Pacific)	
Power source		220–240 V, 50/60 Hz, 4.3 Amps (Asia Pacific)		
CONSUMABLES				
AIO toner cartridges (K) (Regular yield)		Black: Approx. 3,500 pages		
AlO toner cartridges (K) (High yield)		Black: Approx. 7,000 pages		
		2		
Consumable yield mea				
Shipped with Starter T		z Iy (Black: Approx. 1,000 pages)		
Shipped with Starter T OPTIONS		ly (Black: Approx. 1,000 pages)	less LAN) and Wi-Fi Direct	
Shipped with Starter T				



www.ricoh-ap.com

RICOH ASIA PACIFIC PTE LTD 30 Cecil Street, #13-01/08 Prudential Tower, Singapore 049712 Phone: +65 6830 5888, Fax: +65 6830 5880

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2022 Ricoh Asia Pacific Pte Ltd. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Asia Pacific Pte Ltd.

mopria

Apple AirPrint

RICOH @Remote

RICOH