RICOH
imagine. change.

Full Colour Multifunction Printer

IM C2010/IM C2510
IM C3010/C3010EX
IM C3510/C3510EX
IM C4510
IM C6010
IM C7010

☑ Printer ☑ Copier ☑ Scanner ☑ Fax

IM C2010 20 ppm	IM C2510 25 ppm	IM C3010 IM C3010EX 30 ppm	IM C3510 IM C3510EX 35 ppm
IM C4510 45 ppm	IM C6010 60 ppm	IM C7010 70 ppm	

Let’s make your print infrastructure a gateway to your digital workspace

As workstyles evolve, digitalisation, and agility are essential for your organisation to remain competitive. The new Ricoh IM C Series unlock the value of your print infrastructure with tailored, managed solutions which empower your people, improve efficiency, reduce cost, enhance security and drive sustainability.Innovatively designed, the IM C Series seamlessly integrate with cloud services and offer high-quality print, scanning and workflow automation.

Achieve your sustainability goals

A carbon neutral future

The IM C Series significantly reduces energy consumption and paper consumption by digitising workflows through scanning; helping to reduce your carbon footprint and costs.

More energy savings

The IM C Series boasts industry-leading low TEC values and automatic eco-mode energy saving (0.3W) when in sleep mode. An innovative new toner that fuses at a lower temperature, resulting in the ideal sustainability at its core.

More recycled plastic

Designed for sustainability across its lifecycle, the IM C Series is made using 50% post-consumer recycled plastic while PET toner bottles are produced from 100% recycled plastic. Plastic packaging is reduced by 54% thanks to a more sustainable material and no excess packaging.

Secure and efficient

Ongoing security

RICOH Always Current Technology provides security updates automatically. New security tools include WPA3 authentication for wireless encryption and the latest hardware security module. You can also restrict networks by port name and protocol as well as IP address.

Flexible authentication options

The IM C Series comes with a wide range of authentication, including user code, basic authentication, Windows and LDAP authentication, and card-based access to the device, to minimise the risk of data breaches.

Improved admin management system

Privileged admin account control with unlimited MFP administrator accounts and customisable permissions. This eliminates risks related to sharing IDs and can be linked to user ID systems including Windows and LDAP platforms.

Enhanced productivity and seamless employee experience

Third-generation Smart Operation Panel

The new Smart Operation Panel has been upgraded for an even more intuitive and enjoyable experience. Brightness, touch sensitivity and position detection have been improved for optimal access to the device's resources and functions.

Improved user experience

- Android OS 10 for better security and usability
- Faster CPU, high RAM memory and enhanced performance
- Enhanced accessibility to device, tiltable for better visibility & new capacitive touch sensor
- Fast wake up time from sleep mode

Efficiencies in paper handling

New peripherals ensure professional results with automated finishing possibilities. The SPDF capably handles high volumes, special paper and card types. High-end options include a hybrid and booklet finisher for that extra touch.

Supporting your entire digital journey now and into the future

Scanning and automation

Scanning creates digitised documents that can automate processes like invoice and contract management. Uploading documents into your systems for archiving or as part of a workflow is now simpler with Ricoh's software.

Document management storage

Our scalable document management applications drive significant cost savings alongside process improvements. By taking print to the cloud, you can set location-aware printers and enable users to print anytime, anywhere.

Transitioning to the cloud

Our cloud software solutions are easy to integrate with your existing IT infrastructure, allowing you to enhance the capabilities of your print device. You can also securely connect mobile devices to carry out tasks from your phone or tablet.

IM C2010/IM C2510/IM C3010/IM C3010EX/IM C3510/IM C3510EX/IM C4510/IM C6010/IM C7010

	IM C2010 (ARDF)	IM C2510 (ARDF)	IM C3010 (SPDF) IM C3010EX (ARDF)	IM C3510 (SPDF) IM C3510EX (ARDF)	IM C4510 (SPDF)	IM C6010 (SPDF)	IM C7010 (SPDF)
GENERAL							
Warm-up time	24 seconds	24 seconds	24 seconds	24 seconds	23 seconds	23 seconds	24 seconds
First copy speed: BW / Full color	5.1 / 7.4 seconds	5.1 / 7.4 seconds	4.5 / 6.9 seconds	4.5 / 6.9 seconds	3.6 / 5.4 seconds	2.9 / 4.2 seconds	2.9 / 4.2 seconds
Continuous output speed	20 ppm	25 ppm	30 ppm	35 ppm	45 ppm	60 ppm	70 ppm
Memory: standard	6 GB (2 GB mainframe + 4 GB SOP)						8 GB (4 GB mainframe + 4 GB SOP)
SSD: standard/max.	256 GB / 1 TB						
Document Feeder capacity	100 sheets	100 sheets	220 / 100 sheets	220 / 100 sheets	220 sheets	220 sheets	220 sheets
Weight (kg)	89.7	89.7	99.3 / 92.9	99.3 / 92.9	100.8	100.8	106
Dimensions WxDxH (mm)	587 x 701 x 913	587 x 701 x 913	587 x 701 x 963 / 587 x 701 x 913	587 x 701 x 963 / 587 x 701 x 913	587 x 701 x 963	587 x 701 x 963	587 x 724 x 963
Power source	220 - 240 V, 50 - 60 Hz						
COPIER							
Multiple copying	Up to 999 copies						
Resolution	600 dpi						
Zoom	From 25% to 400% in 1% steps						
PRINTER							
First print speed: BW / Full color	4.5 / 7 seconds	4.5 / 7 seconds	4 / 6.6 seconds	4 / 6.6 seconds	3.2 / 5.2 seconds	2.4 / 3.8 seconds	2.2 / 3.7 seconds
CPU	Intel Apollo Lake Atom 1.3 GHz				Intel Apollo Lake Atom 1.6 GHz		
Printer language: standard	PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation)						
Printer language: option	Genuine Adobe® PostScript®3™, PDF Direct from Adobe®						
Print resolution: maximum	4,800 x 1,200 dpi (equivalent)						
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B						
Network interface: option	Wireless LAN (IEEE 802.11 a/b/g/n/ac), Additional NIC (2nd port)						
Mobile printing capability	Apple AirPrint, Mopria®, NFC, Ricoh Smart Device Connector						
Windows® support	Windows® 10, Windows® 11, Windows® Server 2016, Windows® Server 2019, Windows® Server 2022, Windows® Server 2025						
Mac OS support	Macintosh OS X v10.15 ขึ้นไป						
UNIX environments	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX						
SAP® environments	SAP® R/3®, SAP® S/4®						
Other supported OS	IBM iSeries						
SCANNER							
Scanning speed: (A4 LEF, 200 dpi, B/W, Full color)	80 ipm	80 ipm	150 ipm (simplex) 300 ipm (duplex) / 80 ipm	150 ipm (simplex) 300 ipm (duplex) / 80 ipm	150 ipm (simplex) 300 ipm (duplex)	150 ipm (simplex) 300 ipm (duplex)	150 ipm (simplex) 300 ipm (duplex)
Resolution	100 x 100 dpi, 200 x 200 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi, 1,200 x 1,200 dpi* (*supported only with A5 or smaller paper size.)						
File formats	Single Page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF/A, Single page Encryption PDF, Multi page Encryption PDF, Single/multi OCR (optional)						
Scan modes	E-mail, Folder, USB						
FAX							
Circuit	PSTN, PBX						
Transmission speed	3 seconds						
Modem speed: max.	33.6 Kbps						
Resolution: standard	8x3.85 line/mm, 200x100 dpi						
Resolution: option	16x15.4 line/mm, 400x400 dpi						
Compression method	MH, MR, MMR, JBIG						
Scanning speed (A4 LEF)	68 spm	68 spm	90 spm / 68 spm	90 spm / 68 spm	90 spm	90 spm	90 spm
Memory: standard	4 MB, (320 pages)						
Memory: maximum	60 MB, (4,800 pages)						
PAPER HANDLING							
Recommended paper size	Standard tray: SRA3, A3, A4, A5, A6, B4, B5, B6, Envelopes / Optional tray: SRA3, A3, A4, A5, A6, B4, B5, B6, Envelopes / Bypass tray: SRA3, A3, A4, A5, A6, B4, B5, B6, Envelopes / Custom Size (Width: 90-320mm, Length: 148-457.2mm (Copy/Document server) 148-1,260mm (FAX/Printer))						
Paper input	Standard: 1,200 sheets I Maximum: IM C2010, IM C2510 ; 2,300 sheets / IM C3010, IM C3010EX, IM C3510, IM C3510EX, IM C4510, IM C6010, IM C7010 ; 4,850 sheets						
Paper output	Standard: 500 sheets I Maximum: IM C2010, IM C2510, IM C3010, IM C3010EX, IM C3510, IM C3510EX ; 1,625 sheets / IM C4510, IM C6010, IM C7010 ; 3,625 sheets						
Paper weight	Trays: 60 - 300 g/m², Bypass: 52 – 300 g/m², Duplex: IM C2010, IM C2510 ; 52 - 169 g/m² / IM C3010, IM C3010EX, IM C3510, IM C3510EX, IM C4510, IM C6010, IM C7010 ; 52 - 256 g/m²						
Paper types	Plain paper, Recycle paper, Special paper, Color paper, Letterhead, Cardstock, Preprinted paper, Bond paper, Coated paper, Envelope, Gloss paper, Label paper						
ECOLOGY							
TEC**	0.20 kWh/week	0.25 kWh/week	0.30 kWh/week	0.35 kWh/week	0.45 kWh/week	0.67 kWh/week	0.81 kWh/week

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

1x 550-sheet paper tray (IM C4510, IM C6010 only), 2x 550-sheet paper tray, 2,000-sheet Large capacity tray, 1,650-sheet side Large capacity tray, 1,000-sheet Hybrid finishe, 3,000-sheet finishe, 1,000-sheet Booklet finishe, 3,000-sheet booklet finishe, 250-sheet Internal finishe, 500-sheet Internal finisher (IM C4510, IM C7010 only), Stapleless internal finish, Internal multi-fold unit, Internal shift tray (IM C4510, IM C6010 only), One-bin tray, Output jogger unit

OTHER OPTIONS

Fax unit, G3 Interface, Fax connection unit, Fax memory unit, Caster table, Memory unit, Side Tray (IM C4510, IM C6010 only), Banner paper guide tray, Punch units, IPDS unit, PostScript 3, IEEE 802.11 a/b/g/n/ac, Device server unit, File format converter, OCR unit, Page keeper, Imageable area extension unit, ADF handle, Counter I/F unit, NFC card reader, EFI controller, Unicode Font Package for SAP, Card reader cover, SSD 1 TB option, Enhanced Security SSD, Bridge unit, Toner bottle lock, Stapleless unit, FAX stamp, Antimicrobial screen protector, HDD Option

CONSUMABLES*							
Standard Toner (K/CMY)	30,000 / 18,000	30,000 / 18,000	40,000 / 28,000	40,000 / 28,000	42,000 / 28,000	42,000 / 28,000	42,000 / 28,000
Low-yield Toner (K/CMY)	16,500 / 5,500	16,500 / 5,500	-	-	-	-	-

* Consumable yield based on 3p/j5% coverage on A4 | ** It is a reference value based on the ENERGY STAR Ver.3.0 test method.

RICOH imagine. change.

RICOH THAILAND LTD

341 Onnuj Road, Prawet, Prawet, Bangkok 10250 I Website : www.ricoh.co.th

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2023 Ricoh Asia Pacific Pte Ltd. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Asia Pacific Pte Ltd.